

# BIOFIT

Answers are in our nature.

## Build Your Custom Chair



UUR-M-RC-T-ATF-ARS-06>BLACK

[https://mychair.biofit.com/build/UUR-M-RC-T-ATF-ARS-06%3EBLACK?  
market=laboratory&series=UU&style=foundation&upholstered=nonUpholstered](https://mychair.biofit.com/build/UUR-M-RC-T-ATF-ARS-06%3EBLACK?market=laboratory&series=UU&style=foundation&upholstered=nonUpholstered)

## Component Descriptions

**Market**

Laboratory

Revolutionary advancements that address the unique postures and motions of science professionals to time-honored multidiscipline ergonomic designs.

**Style**

Foundation

**Upholstered**

Non-Upholstered

**Seat**

U - Urethane Chair

Black, self-skinned urethane seat with waterfall front, shaped rear edge and 0.09375" ventilating ribs; measures 18.5" wide x 17" deep x 1.5" thick.

**Performance Package**

06 - Black Metal Parts

Metal parts coated in black powder coated finish for standard working environments.

**Backrest**

U - Urethane

Black, self-skinned urethane backrest with integral lumbar support and 0.09375" ventilating ribs; measures 16.5" wide x 12.5" high.

**Base**

R / GR - Reinforced Composite

Five-legged composite base with caster-to-caster diameter of 25.6" and maximum width of 24.4". T-cross-section legs ensure cleanability, and endure test loads of 1.5-2x BIFMA strength requirements. Features standard 50mm, steel-reinforced, tapered hub (1° 26' 16" (Morse) taper) with gauge line elevation of 113mm from the caster insert plane. The base is cast out of glass-filled nylon.

**Seat Height**

M - Medium

For medium height work surfaces such as workbenches 30" to 37" high. Provides a range of 18" - 25".

**Casters / Glides**

RC - Resistance Caster

Two inches in height, with dual soft-wheels. Casters resist movement when the seat is unoccupied. Plastic collar around caster stem to match base. Standard casters have grey

tread.

### Controls

T / E1 - Task

Control allows function of the seat height activation and backrest adjustments by means of easily engaged levers which can be activated from the seated position. Seat tilt is fixed at 3-1/2° rearward while the backrest adjusts 8° forward and 13° rearward.

### Footring

ATF - Adjustable Tubular Footring

Easily raise or lower this 20-inch diameter cast aluminum footring by loosening and retightening its manual adjustment knob. Recommended for models with with aluminum (A), reinforced composite (R) or wide aluminum (W) bases with seat heights greater than 22 inches.

### Arms

ARS

Height and width adjustable armrests with black self-skinned urethane pads.

### Under Seat Upholstery

No Under Seat Upholstery

### Memory Foam

No Memory Foam

### Upholstery

Black

### Series

UniqueU

Durable UniqueU Series chairs have easy-to-clean seats and backrests that resist water, chemicals, paints and more. Highly versatile, they are available in configurations ranging from harsh work environments to ISO 6 clean rooms.



**WARNING:** This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

© 2023. BioFit Engineered Products. All rights reserved.